

**Reference : C-30H30 8-8 NB**




The Fixolite box is a 6 m long prefabricated lintel box designed to receive a closure (roller shutter, BSO, etc.). The box consists of an inverted U-shaped, fire-retardant expanded polystyrene (30 kg/m<sup>3</sup> density) shell reinforced with steel mesh. The side walls are fitted with aluminum rails.

**Traditional model box.** This box is the most economical and offers good performance. The box is certified by Technical Advice to the CSTB.

Type	30H30
Outer rail ref.	827
Inner rail ref.	827
Finishing	Ribbed polystyrene
Color	Blue polystyrene
Compatible cheek	J-30
Certification	<a href="#">CSTB 16-11-634</a> (translated)
Thermal conductivity	U = 1.43 W/m <sup>2</sup> .K
Thermal resistance*	R = 0.7 m <sup>2</sup> .K/W
(*) R: thermal resistance (m <sup>2</sup> .K/W) taking into account a $\lambda$ coefficient of 0.0374 W/m.K after application of a safety coefficient of 1.15.	
Weight	2.04 kg/m
Reaction to fire	class E (EN ISO 11925-2/EN 13 501)
Air permeability	c*3 class
Acoustic perf. (Dn <sub>w</sub> )	49 dB
<b>Components</b>	
Aluminium (recycl. 85%)	0.57 kg/m
Steel (recycl. 96.5%)	0.76 kg/m
Polystyrene (recycl. 10%)	0.71 kg/m
-	0.0 kg/m
<b>Total</b>	<b>2.04 kg/m</b>

**Finishing (Ribbed polystyrene)****Box dimensions**

Width	298 mm
Height	295 mm
Tunnel	246 mm
External side	26 mm
Internal side	26 mm

**Rail diagram****English version:**[https://fixolite.eu/doc/C-30H30\\_8-8\\_NB.en.pdf](https://fixolite.eu/doc/C-30H30_8-8_NB.en.pdf)**Version française:**[https://fixolite.eu/doc/C-30H30\\_8-8\\_NB.fr.pdf](https://fixolite.eu/doc/C-30H30_8-8_NB.fr.pdf)